4DShape



3D continuous linear inclinometer

YOUR CHALLENGES

- Obtain **reliable** and **precise** measurements to understand structural behaviour
- Observe in real-time 3D deformation of soil or structures
- Use a **compact instrument solution**, that can be adapted to your project's specific requirements



OUR SOLUTION






4DShape is an **all-in-one solution** that uses a flexible chain of 3D inclinometers to continually and automatically monitor **millimetric movements** in **soils** and on **structures**.

A relatively recent innovation based on MEMS (Micro Electromechanical Sensors) technology, it provides an efficient, **effective** and **optimised solution** for many applications.

Composed of **rigid segments** with flexible joints, the 4DShape can be installed in a borehole in the soil or on the surface of a structure vertically or horizontally, inclined or in an arc, without any orientation limit.

THE BENEFITS

- Data with millimetric precision available in real time
- Compact size and low visual impact
- $\bullet \textbf{Excellent sampling} \ \text{with 3 sensors per segment, with segment length availability down to 250 } mm \\$
- Versatility: measurement of buildings, linear infrastructure or in the ground
- A long-term solution requiring little maintenance
- A **tailormade automatic warning system** when used in conjunction with our Gesocope or Beyond online platform



Sixense's

- Our reputation for excellence is built on our client's satisfaction.
- The worldwide specialist in usable, accurate data.
- Close collaboration with the manufacturer.
- Proactive maintenance for managing and following data quality for accurate and useful measurements.

CONTACT US

> monitoring@sixense-group.com

4DShape

3D continuous linear inclinometer



TECHNICAL PRINCIPLES

- Each 4DShape segment contains three inclination MEMS, a microprocessor and a digital temperature sensor.
- The sensor's **measurement range** is **360**°, allowing **installation** vertically, horizontally or on an inclined plane.
- The total length of the 4DShape equipment is determined according to the project's requirements.
- 4DShape is connected to a datalogger to obtain continuous and automatic measurements.



APPLICATIONS



Its **robustness**, **versatility of installation** and **precision** means that 4DShape has **many different applications**:

- Automated measurements of **boreholes** (automatic vertical profiles)
- Tunnel and gallery **convergence** measurements
- Settlement measurements along horizontal profiles (embankments, rail tracks, etc.),
- Deformation measurements of vertical structures (walls, columns, etc.),

SPECIFICATIONS & LIMITATIONS


- **Segment length:** down to 250 mm Typically 500 mm in all orientations and 1 m in horizontal.
- Standard length of 4DShape: 1 m to 150 m
- Diameter: 23 mm
- · System precision:
- +/- 0.5 mm for 30 m length
- Segment resolution:
- +/- 1 arc second, ie. 0.00067°

Measurement range:

- 3D measurements up to +/- 60° from vertical Beyond +/- 60° 2D measurements only (the azimuth variations aren't known when approaching horizontal)
- Operating temperature: -35°C to +60°C
- Waterproof to 980 kPa
- **High frequency measurement:** Please contact us.
- Maximum cable length: Please contact us.

ASSOCIATED TOOLS AND SERVICES

- A **turnkey solution** from installation to providing managed data in real time on a dedicated platform
- Automatic alarms, data validated by our engineers
- **Geotechnical** and **structural** expertise, permitting superior understanding of recorded measurements
- 4DShape is one of the solutions in our toolbox, we always optimise our solutions to your requirements



REFERENCES

- New Princess Grace Hospital, Monaco
- Chavanne Tunnel, France
- International Abu Dhabi Airport, UAE
- Microtunnelling under railway, Pont du Château, France
- Grand Paris Express:
- Line 14 South, Lot GC01, Line 15 South Lot T2A

CONTACT US

> monitoring@sixense-group.com